THERMO-DIFFUSION IN THE TUNGSTEN-BERYLLIUM SYSTEM

by

R. M. Arzhanyi R. M. Volkova D. A. Prokoshkin

<u>Izvestiya</u> <u>Akademii Nauk, SSSR, Metalurgiya i Toplivo</u> No. 6, 162-166 (1962)

Translated from the Russian

DISTRIBUTION UNLIMITED

Translation Branch
Redstone Scientific Information Center
Research and Development Directcrate
U.S. Army Missile Command
Redstone Arsenal, Alabama 35809

1. Introduction

Of all the metals in nature tungsten possesses the highest melting temperature (3410° C). The elastic modulus of tungsten ($40,600 \text{ kg/mm}^2$) exceeds that of such important metals for technology as tantalum, molybdenum, and niobium. The ability of tungsten to maintain satisfactory mechanical properties at elevated temperatures above 2000° C makes it attractive as a highly heat resistant material.

However, in a number of cases it has to be taken into consideration that tungsten begins to oxidize rapidly if heated to 400-500°C in air. With further rise in temperature the oxidation of tungsten begins to become more intense; the trioxide of tungsten which forms on the surface of the metal at temperatures in excess of 800°C has a high vapor pressure, and therefore its evaporation begins. ¹

We have conducted an investigation on surface alloying of tungsten by various elements separately and in combinations. It should be noted that only few works have been published on surface alloying of tungsten. ²⁻⁵ The method of thermodiffusional surface alloying not only permits information on surface hardening of the metal, but also on the phase composition of systems, on diffusion processes, energy characteristics of the phases, and other information.

The present work presents data on the W-Be system. Beryllium is interesting because it possesses such properties as low specific weight for comparatively high durability, good stability against corrosion, and possesses relatively high temperature of melting (1315 $^{\circ}$ C).

The system W-Be has been studied very little. Reference 7 indicates the existence of a WBe $_2$ phase, having a hexagonal structure with lattice parameters a = 4.437, c = 7.274 kX, and another phase of composition MoBe $_{12}$. This phase has a volumetrically centered tetragonal structure with lattice parameter a = 10.14, c = 4.23 Å. Reference 8 notes the existence of phase WBe $_{20}$, having a marginally centered cubic grid with a lattice parameter a = 11.64 Å.

2. Surface Alloying

In the work on thermodiffusion of surface alloying, tungsten rods were used. They had a purity of 99.95 percent, were pressed, baked, and then hammered to a diameter of 10 mm. The microhardness of the rods was 450 kg/mm^2 . The thermodiffusional saturation of tungsten samples was conducted with beryllium of 99.8 percent purity, at temperatures of 900-1200°C with various soaking periods.

Figure 1 shows the kinetics of the phases growth in the diffusion zone at constant temperature (1100° C) and variable duration of the process. From the graph it is evident that the diffusion proceeds according to a parabolic law. An identical dependence is manifested as well in a case of interaction of beryllium with molybdenum and niobium. 9,10

Dissimilarity in the thicknesses of various phases in the diffusion zone depends on several factors, and first of all on the rate of diffusion in the corresponding phase.

Utilizing the obtained data, it is possible to compute approximately temperature dependences of coefficients of diffusion in each phase:

for phase WBe₂₄

$$D = 1.175 \cdot 10^{-3} \exp(-33,800/RT) \tag{1}$$

for phase WBe₁₂

$$D = 2.36 \exp(-66, 950/RT)$$
 (2)

for phase WBe₂

$$D = 1.10 \cdot 10^{-4} \exp(-33,115/RT). \tag{3}$$

In the process of saturation of beryllium, on the surface of the tungsten sample there forms a diffusion zone of complex composition and structure. The microstructure of diffusion layers, obtained at a saturation temperature of 1110°C in the course of four hours, is presented in Figure 2. An analogous structure is obtained as well with saturation temperatures of 900-1200°C.




Figure 1. The Kinetics of Phase Growth in the Diffusion Zone at a Saturation Temperature of 1100°C:

1) First Layer, 2) Second Layer, and 3) Third Layer

Diffusion proceeds with a front with a simultaneous formation of several layers. The internal layer, directly adhering to the metal (tungsten), has clearly defined boundaries with jagged edges, testifying to the now uniform diffusion process in microsections.

A Roentgen-spectral analysis* has shown that the chemical composition of the internal layer corresponds to phase WBe₂ (Figure 3); X-ray investigations have shown that this layer has a crystalline structure type C14, hexagonal (spatial group P6₃/m μ) with lattice parameters: a = 4.446, b = 7.347 kX. The structure of the internal diffusion layer and the lattice parameter determined by us agree with the data on phase WBe₂, obtained through investigation of alloys in reference 7. The microhardness of the layer is very high: 2188 kg/mm².

The second layer, adhering to phase WBe₂ from the outside is colored grey by the reagent, has somewhat uneven delineation of boundaries and gives evidence to the unevenness of diffusion in microvolumes. In the spectrogram curve (Figure 3) this phase is shown as a compound, corresponding to the chemical composition of formula WBe₁₂.

X-ray analysis shows that this layer represents a WBe_{12} compound having a body-centered tetragonal lattice with periods a = 7.29 and c = 4.28 kX. The structure type of C11a, C11c is spatial group 14 m μ^{-1} .

Phase WBe₁₂ which was discovered by us, corresponds to formula MoBe₁₂ in chemical composition. However, the lattice parameters differ significantly from those indicated in reference 7. A check invariably verified our data. The deviations were insignificant, which is due to the small region of homogeneity of the WBe₁₂ phase.

Comparison with the analogous beryllide of niobium $NbBe_{12}$, which also has volume-centered tetragonal lattice with lattice parameters of a = 7.376 and c = $4.280~kX^{10}$ i. e., close to the ones found by us for WBe_{12} , indicates the correctness of the WBe_{12} lattice parameter values that were obtained. The atomic radii of tungsten (1.40) and molybdenum (1.39) are close; taking into consideration the analogy in chemical properties of these elements, similar lattice parameters in analogous compounds are expected.

Thus, it may be considered credible that a WBe_{12} coumpound with volume-centered tetragonal structure exists and that it has the lattice parameters discovered by us.. The microhardness of the WBe_{12} phase (1145 kg/mm²) is significantly lower than the WBe_2 phase hardness.

^{*}Analysis was conducted with participation of E. Marchukova.

The external layer, bright, weakly etched by the reagent, has a relatively great thickness. X-ray analysis of the layer indicates a chemical composition, corresponding to the WBe_{24} compound (Figure 3).

An X-ray pattern of the layer is indexed according to the tetragonal system. The computation gave the lattice parameters values of a = 7.849 and c = 12.730 kX.

In the diffusion zone of system W-Be, phase WBe $_{20}$ with a cubic structure ($a=11.64~\mbox{\sc A}$) indicated in reference 8, is not discovered. The phase found by us is formed in the diffusion zone in the form of a large layer. It has a far greater homogeneity area in comparison with other beryllides of tungsten and it would be admissible to consider the possibility of its inclusion in the WBe $_{20}$ composition, but based on data contained in reference 8, the WBe $_{20}$ compound has an entirely different crystalline structure than WBe $_{24}$. Consequently the problem of the existence of phase WBe $_{20}$ remains uncleared.




Figure 2. Diffusion Layer Microstructure on the Surface of a Tungsten Sample with Saturated Beryllium: 1100°C, Time 4 Hours (X 450)

The hardness of the WBe_{24} phase is equal to $1080~kg/mm^2$. It is less than the hardness of the WBe_2 and WBe_{12} compounds, but considerably greater than tungsten hardness.

The WBe₂₄ phase layer consists of large columnar grains oriented in the direction of the diffusion flow. In places in the internal part of the layer, inclusions were noted that have an identical color with the adhering second layer. In color and X-ray analysis these inclusions may refer to the WBe₁₂ phase. Their formation in the WBe₂₄ external layer may be explained in two ways; first by the nonuniformity of beryllium diffusion in tungsten caused by the presence of dissolved admixtures and submicroscopic inclusions; second, by variation of the beryllium solubility boundary in the WBe₂₄ phase in dependence on temperature. It is not difficult to conceive the solubility boundary variation in the direction of the beryllium concentration increase, as it is schematically shown in Figure 4.




Figure 3. Tungsten Dispersion Curve Along Diffusion Zone Depth.

In this case, at diffusion temperature, the beryllium concentration in the diffusion layer may be obtained from a (Figure 4) on the internal boundary to c on the surface. On cooling after diffusional saturation the beryllium concentration in the WBe $_{24}$ phase will change according to curve a'b. In the external diffusion layer, what remains single phase is only that part of the layer which has a concentration of beryllium within limits bc. The internal part of the layer, having

the WBe₂₄ phase will change according to curve a-b. In the external diffusion layer, what remains single phase is only that part of the layer which has a concentration of beryllium within limits b-c. The internal part of the layer, having




Figure 4. Schematic Representation of Part of a Diagram of the State of the W-Be System

the beryllium concentration within a-b limits becomes heterogeneous. Its base will be WBe_{24} phase, and in it, as in the matrix, will be located the precipitations of the second phase, WBe_{12} . Probably, such a figure was observed on the internal side of the diffusion layer.

The kinetics of tungsten oxidation were studied by many authors. As a result, a lot of experimental and theoretical material has been collected. 11-15 However, there is still little material on the study of oxidized tungsten saturated by various elements.

We have conducted the investigation of oxidation of tungsten saturated by beryllium. The kinetics of oxidation was studied in an atmosphere of air at 900-1200°C by the method of continuous weighing with an accuracy of ± 0.0005 g. The duration of oxidation was 10 hours, with measurements every 15 minutes for the first two hours of oxidation, and every half hour after that.

On the surface of the samples at all investigated temperatures ($1000-1200\,^{\circ}$ C) there forms a thin oxide film (10-15 microns) white-grey in color, closely bonded with basic metal. In interpreting the electrograph of the oxide film, data on the magnitude of the free energy of the beryllium and tungsten oxide formation (BeO-140 Kcal, 1/3 WO₃-60.6 Kcal) were taken into consideration. From these data it is apparent that beryllium has a greater affinity for oxygen than for tungsten (almost 2.5 times).

As has been shown by electrographic analysis, the oxide layer consists of BeO oxide with a hexagonal lattice and a period a = 2.694, c = 4.392 kX. The structure is type B4 spatially homogeneous group $P6_3\mu$.

3. Conclusion

Beryllium and tungsten diffusion at 1000-1200°C proceeds with a front with a simultaneous formation of a number of intermetallic phases of various thickness. The phases are separated between themselves while their boundaries correspond to steps in the concentration curve.

The temperature dependences of the diffusion coefficients have been obtained for each phase.

By means of X-ray and X-ray spectral analysis, the structures and the phase composition of the diffusion layer have been studied. Beryllides of tungsten of the following stoichiometric composition have been established: WBe_{24} , WBe_{12} , and WBe_{2} . The crystal structures of these phases have been established.

LITERATURE CITED

- 1. K. J. Smitels, Volfram Metallurgizdat, 1958.
- 2. G. N. Dubinin, THEORY AND PRACTICE OF DIFFUSIONAL SATURATION OF ALLOYS BY METALS, Investigations in Heat-Resistant Alloys, Compendium, May 1960.
- 3. A. N. Minkevich, DIFFUSIONAL BORIDE LAYERS ON METAL, <u>Physical Metallurgy and Heat Treatment</u>, August 1961, No. 8.
- 4. A. F. Gerasimov, V. N. Konev, and N. F. Timofeiev, INVESTIGATION OF REACTIVE DIFFUSION IN SYSTEMS "METAL COMPLEX GAS" W-S-N SYSTEM, Physics of Metals and Physical Metallurgy, 2, 1961, No. 4.
- 5. P. M. Arzhanyi, P. M. Volkova, and D. A. Prokoshkin, INVESTIGA-TION OF OXIDATION AND STRUCTURE OF OXIDES OF SOME HIGH MELTING METALS, Investigation of Heat Resistant Alloys, 1962, No. 9
- 6. D. White and J. Berka, BERYLLIUM, Translated from English, Edited by B. Reifman, Foreign Literature Publication, 1960.
- 7. L. Misch, Metallwirtschaft, <u>15</u>, 1936, pp. 163-166.
- 8. R. M. Paine and J. A. Carrabine, SOME NEW INTERMETALLIC COMPOUNDS OF BERYLLIUM, <u>Acta Crystallographics</u>, <u>13</u>, Part 8, August 1960, pp. 575-684.
- 9. P. M. Arzhanyi, INVESTIGATION OF PHASE COMPOSITION OF DIFFUSION LAYER, Compendium of Investigations of Heat Resistant Alloys, Publication of Academy of Sciences, USSR, 1959, No. 5, pp. 199-202.
- 10. P. M. Arzhanyi, P. M. Volkova, and D. A. Porkoshkin, ON DIFFUSION OF BERYLLIUM AND ALUMINUM IN NIOBIUM, Reports of Academy of Sciences, Metallurgy and Fuel, 1961, No. 2, pp. 119-121.
- 11. O. Kubaschewski and B. F. Hopkins, OXIDATION MECHANISMS OF NIOBIUM, TANTALIUM, MOLYBDENUM AND TUNGSTEN, J. Less. Common Metals, 2, 1960, pp. 172-180.
- 12. V. I. Arkharov and Yu. D. Kozmanov, ON THE PROBLEM OF HIGH TEMPERATURE OXIDATION OF TUNGSTEN, FMM, Publication of Academy of Sciences, USSR, 1956, No. 2, p. 36.

LITERATURE CITED (Continued)

- 13. E. F. Gulbransen and K. F. Andrew, KINETICS OF THE OXIDATION OF PURE TUNGSTEN FROM 500° to 1300°C, <u>J. of the Electrochemical Society</u>, 107, July 1960, No. 7.
- 14. L. Northott, SOME FEATURES OF THE REFRACTORY METALS, J. of Less. Common Metals, 3, April 1961, No. 2, pp. 125-148.
- 15. R. A. Perkins and D. D. Crooks, LOW PRESSURE HIGH TEMPERATURE OXIDATION OF TUNGSTEN, <u>J. of Metals</u>, 1961, p. 90.

(U) DISTRIBUTION

	No. of Copies		No. of Copies
EXTERNAL		U. S. Atomic Energy Commission	1
Air University Library ATTN: AUL3T	1	ATTN: Reports Library, Room G-017 Washington, D. C. 20545	
Maxwell Air Force Base, Alabama 36112	2	U. S. Naval Research Laboratory ATTN: Code 2027	1
U. S. Army Electronics Proving Ground ATTN: Technical Library Fort Huachuca, Arizona 85613	1	Washington, D. C. 20390	1
	1	Weapons Systems Evaluation Group Washington, D. C. 20305	1
U. S. Naval Ordnance Test Station ATTN: Technical Library, Code 753 China Lake, California 93555	1	John F. Kennedy Space Center, NASA ATTN: KSC Library, Documents Section Kennedy Space Center, Florida 32899	2
U. S. Naval Ordnance Laboratory	1		-
ATTN: Library Corona, California 91720		APGC (PGBPS-12) Eglin Air Force Base, Florida 32542	1
Lawrence Radiation Laboratory ATTN: Technical Information Division P. O. Box 808	1	U. S. Army CDC Infantry Agency Fort Benning, Georgia 31905	1
Livermore, California 94550		Argonne National Laboratory ATTN: Report Section	1
Sandia Corporation ATTN: Technical Library	1	9700 South Cass Avenue Argonne, Illinois 60440	
P. O. Box 969 Livermore, California 94551		U. S. Army Weapons Command ATTN: AMSWE-RDR	1
U. S. Naval Postgraduate School ATTN: Library	1	Rock Island, Illinois 61201	
Monterey, California 93940		Rock Island Arsenal ATTN: SWERI-RDI	1
Electronic Warfare Laboratory, USAECOM Post Office Box 205	M 1	Rock Island, Illinois 61201	
Mountain View, California 94042		U. S. Army Cmd. & General Staff College ATTN: Acquisitions, Library Division	2 1
Jet Propulsion Laboratory ATTN: Library (TDS)	2	Fort Leavenworth, Kansas 66027	
4800 Oak Grove Drive Pasadena, California 91103			1
U. S. Naval Missile Center	1	Fort Leavenworth, Kansas 66027	
ATTN: Technical Library, Code N3022 Point Mugu, California 93041		U. S. Army CDC Armor Agency Fort Knox, Kentucky 40121	1
U. S. Army Air Defense Command ATTN: ADSX Ent Air Force Base, Colorado 80912	1	Michoud Assembly Facility, NASA ATTN: Library, I-MICH-OSD P. O. Box 29300	1
	4	New Orleans, Louisiana 70129	
Central Intelligence Agency ATTN: OCR/DD-Standard Distribution Washington, D. C. 20505	4	Aberdeen Proving Ground ATTN: Technical Library, Bldg. 313 Aberdeen Proving Ground, Maryland 2100	1
Harry Diamond Laboratories	1		
ATTN: Library Washington, D. C. 20438		NASA Sci. & Tech. Information Facility ATTN: Acquisitions Branch (S-AK/DL) P. O. Box 33	5
Scientific & Tech. Information Div., ATTN: ATS	NASA 1	College Park, Maryland 20740	
Washington, D. C. 20546		U. S. Army Edgewood Arsenal ATTN: Librarian, Tech. Info. Div. Edgewood Arsenal, Maryland 21010	1

	No. of Copies	No .	of Copies
National Security Agency ATTN: C3/TDL Fort Meade, Maryland 20755	1	Brookhaven National Laboratory Technical Information Division ATTN: Classified Documents Group Upton, Long Island, New York 11973	1
Goddard Space Flight Center, NASA ATTN: Library, Documents Section Greenbelt, Maryland 20771	1	Watervliet Arsenal ATTN: SWEWV-RD Watervliet, New York 12189	1
U. S. Naval Propellant Plant ATTN: Technical Library Indian Head, Maryland 20640	1	U. S. Army Research Office (ARO-D) ATTN: CRD-AA-IP Box CM, Duke Station	1
U. S. Naval Ordnance Laboratory ATTN: Librarian, Eva Liberman Silver Spring, Maryland 20910	1	Durham, North Carolina 27706 Lewis Research Center, NASA	1
Air Force Cambridge Research Labs. L. G. Hanscom Field ATTN: CRMXLR/Stop 29	1	ATTN: Library 21000 Brookpark Road Cleveland, Ohio 44135	-
Bedford, Massachusetts 01730	1	Systems Engineering Group (RTD) ATTN: SEPIR Weight-Patterson Air Force Rase Objo 4543	1
Springfield Armory ATTN: SWESP-RE Springfield, Massachusetts 01101	1	Wright-Patterson Air Force Base, Ohio 4543 U. S. Army Artillery & Missile School	1
U. S. Army Materials Research Agency ATTN: AMXMR-ATL	1	ATTN: Guided Missile Department Fort Sill, Oklahoma 73503	
Watertown, Massachusetts 02172 Strategic Air Command (OAI)	1	U. S. Army CDC Artillery Agency ATTN: Library Fort Sill, Oklahoma 73504	1
Offutt Air Force Base, Nebraska 68113		U. S. Army War College	1
Picatinny Arsenal, USAMUCOM ATTN: SMUPA-VA6 Dover, New Jersey 07801	1	ATTN: Library Carlisle Barracks, Pennsylvania 17013	
U. S. Army Electronics Command ATTN: AMSEL-CB Fort Monmouth, New Jersey 07703	1	U. S. Naval Air Development Center ATTN: Technical Library Johnsville, Warminster, Pennsylvania 1897	1
Sandia Corporation ATTN: Technical Library	1	Frankford Arsenal ATTN: C-2500-Library Philadelphia, Pennsylvania 19137	1
P. O. Box 5800 Albuquerque, New Mexico 87115 ORA(RRRT)	1	Div. of Technical Information Ext., USAEC P. O. Box 62 Oak Ridge, Tennessee 37830	1
Holloman Air Force Base, New Mexico 88		Oak Ridge National Laboratory	1
Los Alamos Scientific Laboratory ATTN: Report Library P. O. Box 1663 Los Alamos, New Mexico 87544	1	ATTN: Central Files P. O. Box X Oak Ridge, Tennessee 37830	
White Sands Missile Range ATTN: Technical Library	1	Air Defense Agency, USACDC ATTN: Library Fort Bliss, Texas 79916	1
White Sands, New Mexico 88002 Rome Air Development Center (EMLAL-1) ATTN: Documents Library Griffiss Air Force Base, New York 1344	1	U. S. Army Air Defense School ATTN: AKBAAS-DR-R Fort Bliss, Texas 79906	1

Code USS-T (Translation Section)

Washington, D. C. 20546

UNCLASSIFIED

Security Classification					
DOCUMENT CONT			-		
(Security classification of title, body of abstract and indexing					
Redstone Scientific Information Center		2. REPORT SECURITY CLASSIFICATION Unclassified			
Research and Development Directorate		26. GROUP			
U. S. Army Missile Command Redstone Arsenal, Alabama 35809		N/A			
THERMO-DIFFUSION IN THE TUNGSTEN-BER	YLLIUM SYST	ГЕМ			
Izvestiya Akademii Nauk, SSSR, Metalurgiya i	Toplivo, No. 6	6, 162-166	(1962)		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Translated from Russian					
5. AUTHOR(5) (First name, middle initial, last name)					
P. M. Arzhanyi, R. M. Volkova, D. A. Prokos	shkin				
6. REPORT DATE	78. TOTAL NO. OF	PAGES	7b. NO. OF REFS		
21 July 1967	10		15		
8a. CONTRACT OR GRANT NO.	98. ORIGINATOR'S	REPORT NUM	BER(S)		
N/A b. Project no.	}				
	RSIC-68	8			
N/A c.	9b. OTHER REPORT NO(5) (Any other numbers that may be assigned this report)				
d.	AD_				
10. DISTRIBUTION STATEMENT					
Distribution of this document is unlimited.					
II. SUPPLEMENTARY NOTES	12. SPONSORING M	ILITARY ACT	IVITY		
None	Same as No	o. 1			
13. ABSTRACT					
An investigation was conducted on the surfa separately and in combinations. It was found the 1000-1200°C proceeds with a front with a simular phases of various thickness. The phases are suboundaries correspond to steps in the concentration. The temperature dependences of the diffusion By means of X-ray and X-ray spectral analysis diffusion layer have been studied. Beryllides of composition have been established: WBe24, WB phases have also been established.	hat beryllium a ltaneous forma eparated betwe ation curve. ion coefficients a the structure of tungsten of t	and tungste ation of a n een themse s have been and the pl he following	en diffusion at number of intermetallic elves while their n obtained for each phase. nase composition of the ng stochiometric		

Security Classification							
4. KEY WORDS		LINK A		LINKB		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT	
Surface alloying				· '			
Thermodiffusion		l '					
	1				1		
Diffusion layer							
Microstructure	!						
Lattice parameter							
Tungsten oxide							
Beryllium oxide							
]						
	1						
	1			[[[
		1					
	İ	ł		Ì			
	İ	1					
		<u> </u>					
		į		1			
					}		
		l		ļ]		
	j	<u> </u>]]		
		1					
			1				
		ļ		!	'		
				İ			
1		i					
			1				
	ł	ł	ł		ł		
		1					
		}	ŀ	l			
	l						
	İ						
		ĺ	ļ		1		
			1]		
		{	ĺ	[
,			1]		
			Į.				
]		1			
		1		1			
		ł	l	l		1	
	Ì	1	1				
	1	1	ł	l			
	1	1		1			
		1		L		Ĺ	

UNCLASSIFIED

16

Security Classification